1 REFERENCES

[1] EwaldPeiszer, Thomas Lidy, Andreas Rauber, 2008,"Automatic Audio Segmentation: Segment Boundary and Structure Detection in Popular Music"

[2]George Tzanetakis Perry Cook ,1999, "Multifeature Audio Segmentation for Browsing and Annotation" Proc.1999 IEEE Workshop on Applications of Signal Processing to Audio and Acoustics, New Paltz, New York, pp W99-1 – W99-4

[3] GuojunLu ,2001,"Indexing and Retrieval of Audio: A Survey", pp 269-290

[4] Jessie Xin Zhang1, Jacqueline Whalley1, Stephen Brooks,2004,"A Two Phase Method for general audio segmentation" ,

[5] Jonthan Foote , "Automatic Audio Segmentation Using A Measure of Audio Novelty",

[6] Julien P., Jose´ A. and Regine A.," Audio classification by search of primary Components", PP 1-12

[7]Lie Lu, Hong-Jiang Zhang and HaoJiang, 2002,, "Content Analysis for Audio Classification and Segmentation" ,IEEE Transaction on Speech and Audio Processing, pp 504-516

[8] Lie Lu, Stan Z. Li and Hong-Jiang Zhang, 2008,"Content based audio segmentation using Support Vector Machines"

[9]MateuAguilo, TarasButko, AndreyTemko, ClimentNadeu, 2009,"A Hierarchical Architecture for Audio Segmentation in a Broadcast News Task", PP 17-20

[10] Mauro Cettolo , Michele Vescovi , Romeo Rizzi , Elsevier ,2005,"Evaluation of BIC-based algorithms for audio segmentation", pp 147–170

[11] Michael M. Goodwin and Jean Laroche, 2003,"Audio Segmentation by feature space clustering using linear discriminant analysis and dynamic programming"

[12] Mohammad A. Hague& Jong-Myon Kim, 2012,"An analysis of content-based classification of audio signals using a fuzzy c-means algorithm"

[13] NimaMesgarani, Malcolm Slaney, andShihab A. Shamma, 2006 "Discrimination of Speech from Nonspeech Based on Multiscale Spectro-Temporal Modulations", pp 920-930

[14] P. Krishnamoorthy · Sarvesh Kumar, 2010,"Hierarchical audio content classification system using an optimal feature selection algorithm" , pp415–444

[15] Panagiotis S., Vasileios M., Ioannis K., Hugo M., Miguel B., Isabel T.,"On the use of audio events for improving video scene segmentation",

[16] SamerAbdallah· Mark Sandler ·Christophe Rhodes, Michael Casey,2006 , " Using duration Models to reduce fragmentation in audio segmentation",pp 65:485–515

[17] Shih-Sian Cheng, Hsin-Min Wang, and Hsin-Chia Fu,"BIC-BASED Audio Segmentation by divide and conquer",

[18] Shi Yong, 2007,"Audio Segmentation", PP 1-4

[19]ShoichiMatsunaga, Osamu Mizuno, KatsutoshiOhtsuki, and Yoshihiko Hayashi ,"Audio source segmentation using spectral correlation features for automatic indexing of broadcast news",PP 2103 to 2106

[20]Tara N. Sainath DimitriKanevsky and GiridharanIyengar, 2007 ,"Uusupervised audio segmentation using extended Baum-Welch Transformations" , PP I 209-I 212

[21] TheodorosGiannakopoulos ,AggelosPikrakis , SergiosTheodoridis ,2008, "A Novel Efficient Approach for Audio Segmentation"

[22] Yibin Zhang and JieZhou ,2004, "Audio Segmentation based on Multiscale audio classification" PP IV – 349 to IV – 352

[23] YuxinPeng, Chong-Wah Ngo, Cuihua Fang, Xiaoou Chen, and Jianguo Xiao, "Audio Similarity Measure by Graph Modeling and Matching", pp603-606

[24] ZaıdHarchaoui, F´elicienVallet, Alexandre Lung-Yut-Fong, Olivier Cap, "Regularized Kernel-Based Approach to Unsupervised Audio Segmentation"